Package: vaxineR (via r-universe)

October 31, 2026

Type Package

Title Vaccine Coverage and Outbreak Risk Analysis

Version 0.1.0

Description Provides tools to analyze vaccine coverage data and simulate potential disease outbreak scenarios. It allows users to calculate key epidemiological metrics such as the effective reproduction number (Re), outbreak probabilities, and expected infection counts based on county-level vaccination rates, disease characteristics, and vaccine effectiveness. The package includes historical kindergarten vaccination data for Florida counties and offers functions for generating summary tables, visualizations, and exporting the underlying plot data.

License GPL (>= 3)

Encoding UTF-8

LazyData true

Imports dplyr, tidyr, ggplot2, scales, purrr, tibble, openxlsx

Suggests knitr, rmarkdown

VignetteBuilder knitr

RoxygenNote 7.3.2

Depends R (>= 3.5)

Config/pak/sysreqs libicu-dev

Repository https://peiyuliu-biostats.r-universe.dev

Date/Publication 2025-09-27 15:04:21 UTC

RemoteUrl https://github.com/peiyuliu-biostats/vaxiner

RemoteRef HEAD

RemoteSha 3e386406d2c06f9296d767c8d88a0c0824c626a7

Contents

calc_expected_infections 2
calc_re 3
florida_vaccine_coverage 3
plot_coverage_history 4
plot_outbreak_prob 5
plot_risk_curve 6
prob_major_outbreak 7
prob_sec_case 7
summary_coverage 8
summary_infection_risk 8

Index **10**

`calc_expected_infections` *Calculate the expected number of infections in a cohort*

Description

Calculate the expected number of infections in a cohort

Usage

```
calc_expected_infections(vc, disease, kindergarten_size, VE, r0_custom = NULL)
```

Arguments

`vc`	Vaccination coverage rate (proportion, 0 to 1).
`disease`	Character string: "Measles", "Pertussis", "Chickenpox", or "Custom".
`kindergarten_size`	Integer, the size of the school cohort.
`VE`	Vaccine effectiveness (proportion, 0 to 1).
`r0_custom`	The basic reproduction number (R0) for a custom disease. Required only if 'disease' is "Custom".

Value

The expected number of infected individuals.

Examples

```
calc_expected_infections(vc = 0.85, disease = "Measles", kindergarten_size = 200, VE = 0.97)
calc_expected_infections(
  vc = 0.90, disease = "Custom", kindergarten_size = 150, VE = 0.90, r0_custom = 7
)
```

calc_re *Calculate the effective reproduction number (Re)*

Description

Calculate the effective reproduction number (Re)

Usage

```
calc_re(vc, disease, VE, r0_custom = NULL)
```

Arguments

vc	Vaccination coverage rate (proportion, 0 to 1).
disease	Character string: "Measles", "Pertussis", "Chickenpox", or "Custom".
VE	Vaccine effectiveness (proportion, 0 to 1).
r0_custom	The basic reproduction number (R0) for a custom disease. Required only if 'disease' is "Custom".

Value

The effective reproduction number (Re).

Examples

```
# For a standard disease
calc_re(vc = 0.92, disease = "Measles", VE = 0.97)
# For a custom disease like mumps (R0 approx. 10-12)
calc_re(vc = 0.88, disease = "Custom", VE = 0.85, r0_custom = 11)
```

florida_vaccine_coverage *Kindergarten Vaccination Coverage for Florida Counties*

Description

A dataset containing the percentage of kindergarten students who have completed required immunizations for school entry in Florida counties.

Usage

```
florida_vaccine_coverage
```

Format

A data frame with 748 rows and 3 variables:

County The name of the county in Florida, plus a statewide "Florida" total.

Year The calendar year of the report, from 2016 to 2024.

Coverage_Rate The proportion (0 to 1) of kindergarten students with complete immunizations.

Source

Florida Department of Health, Bureau of Immunization.

---

plot_coverage_history *Plot Historical Vaccination Coverage Rate*

Description

Plot Historical Vaccination Coverage Rate

Usage

```
plot_coverage_history(county_name, save_data_to = NULL)
```

Arguments

county_name	A character vector of county names to plot.
save_data_to	Optional file path to save the plot's data.

Value

A ggplot object.

Examples

```
plot_coverage_history(county_name = c("Florida", "Miami-Dade", "Liberty"))
```

`plot_outbreak_prob` *Plot Outbreak Probability vs. Coverage*

Description

Plot Outbreak Probability vs. Coverage

Usage

```
plot_outbreak_prob(
  disease = "Measles",
  VE = NULL,
  r0_custom = NULL,
  save_data_to = NULL
)
```

Arguments

`disease`	The disease to model. Default is "Measles".
`VE`	Vaccine effectiveness. If NULL (the default), a sensible default is used for the chosen disease (e.g., 0.97 for Measles). A user-provided value (0 to 1) will override the default.
`r0_custom`	The basic reproduction number (R0) for a custom disease. Required only if ‘disease‘ is "Custom".
`save_data_to`	Optional file path to save the plot’s data.

Value

A ggplot object.

Examples

```
# Plot with default VE for Pertussis (~0.85)
plot_outbreak_prob(disease = "Pertussis")
# Override default VE for Pertussis
plot_outbreak_prob(disease = "Pertussis", VE = 0.91)
```

plot_risk_curve *Plot the Risk Curve of Expected Infections*

Description

Plot the Risk Curve of Expected Infections

Usage

```
plot_risk_curve(
  disease = "Measles",
  kindergarten_size = 200,
  VE = NULL,
  r0_custom = NULL,
  save_data_to = NULL
)
```

Arguments

disease	The disease to model. Default is "Measles".
kindergarten_size	The size of the school cohort. Default is 200.
VE	Vaccine effectiveness. If NULL (the default), a sensible default is used for the chosen disease (e.g., 0.97 for Measles). A user-provided value (0 to 1) will override the default.
r0_custom	The basic reproduction number (R0) for a custom disease. Required only if 'disease' is "Custom".
save_data_to	Optional file path to save the plot's underlying data.

Value

A ggplot object.

Examples

```
# Plot with default VE for Pertussis (~0.85)
plot_risk_curve(disease = "Pertussis")
# Plot for a custom disease, requires VE and r0_custom
plot_risk_curve(disease = "Custom", VE = 0.85, r0_custom = 12)
```

prob_major_outbreak *Calculate the probability of a major outbreak*

Description

Calculate the probability of a major outbreak

Usage

```
prob_major_outbreak(Re)
```

Arguments

Re	The effective reproduction number.

Value

The probability of a major outbreak (1 - 1/Re).

Examples

```
prob_major_outbreak(Re = 2.05)
```

prob_sec_case *Calculate the probability of at least one secondary infection*

Description

Calculate the probability of at least one secondary infection

Usage

```
prob_sec_case(Re)
```

Arguments

Re	The effective reproduction number.

Value

The probability of at least one secondary infection.

Examples

```
prob_sec_case(Re = 2.05)
```

summary_coverage *Summarize Vaccination Coverage for a Given Year*

Description

Retrieves and sorts the vaccination coverage rates for all Florida counties for a specified year.

Usage

```
summary_coverage(yr)
```

Arguments

yr	The year to summarize (e.g., 2024).

Value

A tibble with columns 'County' and 'Coverage_Rate' (as a numeric proportion), sorted in descending order of the coverage rate.

Examples

```
# Get a summary of vaccine coverage for 2024
summary_coverage(yr = 2024)
```

summary_infection_risk *Generate an Outbreak Risk Simulation Table*

Description

Creates a summary table of outbreak risk for a given year. The analysis includes scenarios for the statewide average coverage rate as well as for counties at the minimum, maximum, and quartile coverage rates. This function can model pre-set diseases or a custom disease with a user-specified R0.

Usage

```
summary_infection_risk(
  yr,
  disease = "Measles",
  kindergarten_size = 200,
  VE = NULL,
  r0_custom = NULL
)
```

Arguments

yr	The year for the analysis (e.g., 2024).
disease	The disease to model. Choose from "Measles", "Pertussis", "Chickenpox", or "Custom". Default is "Measles".
kindergarten_size	The size of the school cohort. Default is 200.
VE	Vaccine effectiveness. If NULL (the default), a sensible default is used for the chosen disease (e.g., 0.97 for Measles). A user-provided value (0 to 1) will override the default.
r0_custom	The basic reproduction number (R0) for a custom disease. This parameter is required and must be a positive number if ‘disease‘ is set to "Custom".

Value

A data frame containing the formatted risk analysis table.

Examples

```
# Example 1: Standard analysis for Measles in 2024 (uses default VE of 0.97)
summary_infection_risk(yr = 2024, disease = "Measles")

# Example 2: Analysis for Pertussis, overriding the default VE
summary_infection_risk(yr = 2024, disease = "Pertussis", VE = 0.91)

# Example 3: Analysis for a custom disease (e.g., Mumps-like)
summary_infection_risk(yr = 2024, disease = "Custom", VE = 0.88, r0_custom = 11)
```

Index

∗ **datasets**
florida_vaccine_coverage, 3

calc_expected_infections, 2
calc_re, 3

florida_vaccine_coverage, 3

plot_coverage_history, 4
plot_outbreak_prob, 5
plot_risk_curve, 6
prob_major_outbreak, 7
prob_sec_case, 7

summary_coverage, 8
summary_infection_risk, 8